

LENNOX
Innovation never felt so good.®

proven reliability



GWB8-IE

Standard-
efficiency,
gas-fired
water boiler

A reliable way to stay warm and save energy.

Built with the finest materials, including a cast iron heat exchanger and titanium burners, the GWB8-IE boiler offers a high level of innovation and comfort. With efficiency ratings of up to 84.4%, the GWB8-IE can also deliver significant energy savings, compared to an older boiler.

Possibilities beyond “one size fits all”

Available in six different sizes, a Lennox GWB8-IE boiler can be integrated with any existing radiator or underfloor heating system. A choice of natural* or LP gas adds to the boiler’s application flexibility.

Quality you can count on

Highly accurate electronic controls regulate the heat of water as it circulates through radiator piping. Plus, each unit is fire-tested and inspected prior to shipping to ensure the highest possible degree of operating reliability. A 20-year limited warranty on the heat exchanger and a 5-year limited warranty on covered parts** provide additional peace of mind.



GWB8-IE2 Specifications

Model	GWB8-042IE-2	GWB8-075IE-2	GWB8-112IE-2	GWB8-150IE-2	GWB8-187IE-2	GWB8-225IE-2
Heating Efficiency (AFUE)	84.4%	83.4%	83.0%	82.7%	82.3%	82.0%
Dimensions						
HxWxD (in)	29 x 11 x 23-1/4	29 x 14-1/4 x 23-1/4	29 x 17-1/2 x 23-1/4	29 x 20-3/4 x 23-1/4	29 x 24 x 23-1/4	29 x 27-1/4 x 23-1/4
HxWxD (mm)	737 x 279 x 591	737 x 362 x 591	737 x 445 x 591	737 x 527 x 591	737 x 610 x 591	737 x 692 x 591

Note: Due to Lennox’ ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.

Economical, gas-fired heating

The GWB8-IE boiler has many features that provide you years of heating benefits.

- **Electronic Ignition Control** – Monitors water temperature and maximizes efficiency by turning on the burner only when needed.
- **Cast Iron Heat Exchanger** – Designed for years of long-lasting reliability over a range of water flow rates.
- **Thick Fiberglass Insulation** – Minimizes heat and energy loss when the heat exchanger cools down after a cycle.
- **Titanium Burners** – Provide greater resistance to corrosion and oxidation than competitive stainless or aluminized steel burners.

*Shipped as natural gas. Convertible to LP.

**Covered components may be eligible to receive a 10-year limited warranty. Online equipment registration at www.lennoxregistration.com is required within 60 days of installation (except in California and Quebec) or Lennox’ base warranty will apply. Applies to residential applications only. See actual warranty certificate for details.



For a complete list of the registered and common law trademarks owned by Lennox Industries Inc., please visit www.lennox.com.

